

CHAIN LUBRICANT FOOD GRADE



The silicone free, food grade chain lubricant for parts and equipment.

- Excellent for applications involving incidental food contact on food processing equipment
- NSF registered H1 (# 132899)
- Foaming action provides extra penetration and lubrication
- Oily, wet film extends chain life
- Nonflammable

Chain Lubricant Food Grade is available in this size:

Container	Net Fill	Part No.
16 oz.	12 oz. (340 grams) aerosol	06016

Typical applications where Chain Lubricant Food Grade can be used:

- Bottling Equipment
- Bushings
- Casters
- Chains
- Channels
- Conveyors
- Drives
- Filling Equipment
- Food Processing Equipment
- Food Service Carts
- Food Racks
- Machines
- Pins
- Rollers
- Sliding Tracks

General Information

Chain Lubricant Food Grade is an extra-strength lubricant for use on food processing equipment. It is NSF H1 registered (#132899) and ideal for applications involving incidental food contact. Chain Lubricant Food Grade has an oily, wet film and foaming action to provide extra penetration and lubrication. It helps extend chain life and reduces wear caused by friction. Chain Lubricant Food Grade contains no silicone or chlorinated solvents and is safe to use on metal and most plastic surfaces. Chain Lubricant Food Grade has an extension tube for spraying into blind holes.

Material Safety Data Sheets are available upon request.

Properties

Flash Point:

Not flammable by the CSMA Flame Extension

Temperature Range:

20°F – 325°F (7°C – 163°C)

Specific Gravity:

.857 – .867 @ 77°F (25°C)

VOC Content:

15% – 123g/l – 1.03 lbs./gal.

ASTM D 2266 4-Ball Wear Scar Diameter (40 kg. load):

.50 mm

Base Oil Viscosity:

@ 100°F, SUS 205@ 40°C, cST 39.9

Propellant:

Hydrocarbon

